

Command:AFINFO (AFI)

MS2000 and RM2000 Syntax

Shortcut	<i>AFI requires v9.57</i>
Format	AFINFO
Firmware Required	v8.8a

Tiger Syntax

Shortcut	<i>AFI requires v3.61 (Tiger Comm)</i>
Format	[Addr#]AFINFO
Type	Card-Addressed
Firmware Required	v3.27

The AFINFO command is a diagnostic command that displays parameters that control autofocus. It also returns the maximum focus value found during last autofocus run, the original location, and the location after the frame offset was applied.

Example

```
AFINFO
Best Focus:587
Position Preoffset:    0.0002 mm Afteroffset:  -0.0003 mm
Speed : 1    [AF X]
Travel:0.025000 [AF Y]
Frame Offset:3.500000 [AFC Y]
Hill Offset:70 [AF F]
Contrast:10 [AFC X]
Window Size X:98 Y:98 [AL X Y]
Zero ADJ X:50 Y:90 [AFADJ X Y]
ADC Gain:0 [AFADJ Z]
<LF>
```

If the line has square brackets, you can change the parameters with the command inside the brackets: [AF](#), [AFC](#), [AL](#), or [AFJ](#).

If the SAVE_SPACE firmware module is included, it will only display Best Focus, Position Preoffset and Position Afteroffset.

```
Best Focus:587
Position Preoffset:    0.0002 mm Afteroffset:  -0.0003 mm
```

[commands](#), [ms2000](#), [autofocus](#)

From:

<https://docs.asiimaging.com/> - **Applied Scientific Instrumentation**

Permanent link:

<https://docs.asiimaging.com/commands/afinfo?rev=1780263603>

Last update: **2026/05/31 17:40**

