Command:AFINFO (AFI)

MS2000 and RM2000 Syntax

Shortcut	AFI *requires v9.60*
Format	AFINFO
Firmware Required	8.8a

Tiger Syntax

Shortcut	AFI *requires v3.61 (Tiger Comm)*
Format	[Addr#]AFINFO
Type	Card-Addressed
Firmware Required	3.27

The `AFINFO` command is a diagnostic command that displays information about autofocus.

It also displays the maximum focus value found during last autofocus run (`Best Focus`), the original location (`Preoffset`), and the location after the frame offset was applied (`Afteroffset`).

Example

```
AFINFO
Best Focus:587
Position Preoffset:   0.0002 mm Afteroffset:  -0.0003 mm
Speed :  1   [AF X]
Travel:0.025000 [AF Y]
Frame Offset:3.500000 [AFC Y]
Hill Offset:70 [AF F]
Contrast:10 [AFC X]
Window Size X:98 Y:98 [AL X Y]
Zero ADJ X:50 Y:90 [AFJ X Y]
ADC Gain:0  [AFJ Z]
<LF>
```

If the line has square brackets, you can change the parameters with the command inside the brackets: AF, AFC, AL, or AFJ.

If the SAVE_SPACE firmware module is included, it will only display `Best Focus`, `Position Preoffset` and `Position Afteroffset`.

```
Best Focus:587
Position Preoffset:   0.0002 mm Afteroffset:  -0.0003 mm
```

autofocus, commands, ms2000, tiger

From:
https://docs.asiimaging.com/ - **Applied Scientific Instrumentation**

Permanent link:
https://docs.asiimaging.com/commands/afinfo?rev=1788211908

Last update: **2026/08/31 17:31**